# GREEN DIAMOND TO DIAMO

## SAFETY DATA SHEET

Abrasives 8x16, 1636, 1650, 2050, 30x50, 3060 Or a blend of any of the above products

## **Section 1 - Chemical Product and Company Identification**

Product Name: Green Diamond Abrasives

Manufacturer: Green Diamond Performance Materials

PO Box D

Riddle, OR 97469 (541) 874-3111

## Section 2 – Hazard Identification

Physical State: Solid, granular

**Emergency Overview:** Due to the low toxicity of this product, it is not expected

to pose a risk of acute or chronic health effects of released or spilled. However, spills should be immediately cleaned by sweeping or vacuuming.

Target Organs: May cause respiratory irritation upon exposure to high

airborne concentrations. May cause eye irritation if

material contacts eye.

**Potential Acute Health Effects** 

**Eyes:** May cause irritation to eyes **Skin:** May cause irritation or abrasion

**Inhalation:** May cause irritation upon exposure to high airborne

concentrations

**Ingestion:** May cause digestive irritation, but not expected to cause

adverse systemic effects

**Potential Chronic Health Effects** 

Target Organs: Not likely to cause chronic effects to any target organs or

systems

**Medical Conditions Potentially** 

Aggravated by Overexposure: None expected

GHS Health Hazard

Classification:

N/A

N/A

GHS Physical Hazard

Classification:

GHS Signal Word(s):

GHS Hazard Statement(s):

GHS Precautionary

None Required

None Required

Statement(s):

GHS Pictograms: None Required

**NFPA Hazard Classification:** Health: 0, Fire: 0, Reactivity: 0

HMIS Hazard Classification Health: 0, Fire: 0, Reactivity: 0, Protection: K

# Section 3 – Composition / Mixture Ingredient Information

Ingredient (Component)	CAS Number	%wt
SiO2 (Silicates - Amorphous)*	112926-00-8	50.2
MgO (Magnesium Oxide)	1309-48-4	31.4
Fe2O3 (Iron Oxide)	1309-37-1	15.9
Al2O3 (Aluminum Oxide)	1344-28-1	1.6
CaO (Calcium Oxide)	1305-78-8	0.7
Ni (Nickel) and NiO (Nickel Oxide)	7440-02-0	<0.1
Cr2O3 (Chromium Oxide)	1308-38-9	0.1



Abrasives 8x16, 1636, 1650, 2050, 30x50, 3060 Or a blend of any of the above products

Trace Elements and Compounds N/A <0.1

\*Contains no free crystalline silica

## Section 4 - First Aid Measures

**Inhalation:** Remove from exposure situation and move to fresh air. Seek

medical attention if symptoms persist.

**Eye Contact:** Flush eyes with large amounts of water for 15 minutes.

Remove contact lenses, hold eyelids open to ensure thorough flushing. Seek medical attention if eye damage is suspected.

**Skin Contact:** Wash or brush material off skin. If irritation occurs, seek

medical attention.

**Ingestion:** If person is conscious, give large quantity of water and induce

vomiting; however, never attempt to make an unconscious person drink or vomit. Get immediate medical attention.

# Section 5 - Fire-Fighting Measures

Flammability: Non-Flammable, Non-Combustible

Flash Point: N/A Flash Point Method: N/A

Auto-ignition Temperature: Not Established

LEL: N/A
UEL: N/A
Extinguishing Media: N/A
Products of Combustion: None
Fire-Fighting Instructions: None
Fire-Fighting Equipment: None

## Section 6 – Accidental Release Measures

**Spill and Leak Procedure:** Clean spills with broom, vacuum cleaner, shovel or scoop.

Although the toxicity of this product is extremely low, it is advisable to minimize the creation of airborne dust.

**Containment:** Contain spilled material in an appropriate container.

**Regulatory Requirements:** Dispose of waste material in accordance with federal, state and

local solid waste disposal regulations and requirements.

# Section 7 – Handling and Storage

**Handling Precautions:** Avoid generating excessive airborne dust.

**Storage Requirements:** No special storage requirements.



Abrasives 8x16, 1636, 1650, 2050, 30x50, 3060 Or a blend of any of the above products

# Section 8 – Exposure Controls / Personal Protection

## Occupational Exposure Limits\*

	OSHA P	PEL	ACGIH 1	ΓLV	NIOSH RI	ΞL	NIOSH
Ingredient	TWA	STEL	TWA	STEL	TWA	STEL	IDLH
Amorphous Silica <sup>1</sup>	10 mg/m <sup>3</sup>	N/A	10 mg/m <sup>3</sup>	N/A	6 mg/m3	N/A	3000 mg/m <sup>3</sup>
Magnesium Oxide	15 mg/m <sup>3</sup>	N/A	10 mg/m <sup>3</sup>	N/A	N/A	N/A	750 mg/m <sup>3</sup>
Iron Oxide (Dust)	10 mg/m <sup>3</sup>	N/A	5 mg/m <sup>3</sup>	N/A	mg/m³	N/A	2500 mg/m <sup>3</sup>
Aluminum Oxide <sup>2</sup>	10 mg/m <sup>3</sup>	N/A	N/A	N/A	N/A	N/A	N/A
Aluminum Oxide <sup>3</sup>	5 mg/m <sup>3</sup>	N/A	1 mg/m <sup>3</sup>	N/A	N/A	N/A	N/A
Calcium Oxide	5 mg/m <sup>3</sup>	N/A	2 mg/m <sup>3</sup>	N/A	2 mg/m <sup>3</sup>	N/A	25 mg/m <sup>3</sup>
Nickel	1 mg/m <sup>3</sup>	N/A	1.5 mg/m <sup>3</sup>	N/A	0.015 mg/m <sup>3</sup>	N/A	10 mg/m <sup>3</sup>
Chromium Oxide	0.5 mg/m <sup>3</sup>	N/A	0.5 mg/m <sup>3</sup>	N/A	N/A	N/A	N/A

<sup>&</sup>lt;sup>1</sup>As amorphous silica and non-crystalline silicates

#### **Exposure Controls and Personal Protection**

**Engineering Controls:** Provide general or local exhaust ventilation systems in order to

maintain airborne concentrations below occupational exposure limits. Local exhaust ventilation should be used whenever possible to prevent the dispersal of airborne contaminants into the

work area.

**Respiratory Protection:** Obtain professional assistance in selecting the appropriate and

adequate respiratory protection. If necessary, use the appropriate MSHA/NIOSH approved respirator when engineering controls are

not feasible.

**Protective Clothing:** Chemical protective clothing should not be required under normal

circumstances when using this material.

**Hygiene Practices:** Never eat, drink, use tobacco products or apply cosmetics in

areas where hazardous chemicals are used. Employees should wash their hands thoroughly prior to engaging in any of these

activities.

# Section 9 – Physical and Chemical Properties

Appearance and Odor: Grey, green granular solid

Boiling Point: N/A
Vapor Pressure (mm Hg): N/A
Vapor Density (Air = 1): N/A
Specific Gravity (Water = 1): 3.0

<sup>&</sup>lt;sup>2</sup>As total dust

<sup>&</sup>lt;sup>3</sup>As respirable dust

<sup>\*</sup>Refer to federal, state and local occupational exposure limits. Some jurisdictions have published limits that are different from those listed.



Abrasives 8x16, 1636, 1650, 2050, 30x50, 3060 Or a blend of any of the above products

**Melting Point:** 2650 deg. F

**Evaporation Rate:** N/A

Water Solubility: Not soluble in water

## Section 10 – Stability and Reactivity

Stability:StableConditions to Avoid:NoneIncompatibility (Materials to Avoid):NoneHazardous Decomposition or By-Products:None

Hazardous Polymerization: Will Not Occur

Conditions to Avoid: None

Section

## 11 – Toxicological Information

## Toxicity Data:\*

	Toxicity (LD50)	Carcinogenicity		
Ingredient		NTP	IARC	OSHA
SiO2 (Silicates - Amorphous)	>10000 mg/kg	No	No	No
MgO (Magnesium Oxide)	Not Available	No	No	No
Fe2O3 (Iron Oxide)	5500 mg/kg	No	No	No
CaO (Calcium Oxide)	7340 mg/kg	No	No	No
Ni (Nickel) and NiO (Nickel Oxide)	>9000 mg/kg	No	No	No
Cr2O3 (Chromium Oxide)	>10000 mg.kg	No	No	No

Target Organs: May cause respiratory irritation upon exposure to high

airborne concentrations. May cause eye irritation if

material contacts eye.

**Potential Acute Health Effects** 

**Eyes:** May cause irritation to eyes **Skin:** May cause irritation or abrasion

**Inhalation:** May cause irritation upon exposure to high airborne

concentrations

**Ingestion:** May cause digestive irritation, but not expected to cause

adverse systemic effects

**Potential Chronic Health Effects** 

Target Organs: Not likely

Not likely to cause chronic effects to any target organs or

systems

**Medical Conditions Potentially** 

Aggravated by Overexposure: None expected

<sup>\*</sup> See NIOSH for additional toxicity data.



Abrasives 8x16, 1636, 1650, 2050, 30x50, 3060 Or a blend of any of the above products

# Section 12 - Ecological Information

**Ecotoxicity:** No ecotoxicity effects known or anticipated

Environmental Fate:N/AEnvironmental Transport:N/AEnvironmental Degradation:None

## Section 13 – Disposal Considerations

Refer to federal, state and local waste disposal rules and requirements for proper disposal method.

# Section 14 – Transport Information

## **DOT Transportation Data (49 CFR 172.101):**

This product, as produced and offered, is not listed as a Hazardous Material by the Department of Transportation in 49 CFR 172.

## Section 15 – Additional Regulatory Information

This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right to Know Act of 1986 (EPCRA – 40 CFR 372):

Ni (Nickel) and NiO (Nickel Oxide)

7440-02-0

< 0.1%

**Note:** Refer to your federal, state and local environmental, safety and health regulatory agencies for specific additional regulatory requirements in your location.

## **Section 16 – Other Information**

Prepared By: Kerry T. Cooley, CIH, Beacon Northwest, LLC

Revision Date: February 20, 2018

**Disclaimer:** While the information included in this SDS has been obtained from reliable sources, this information is furnished without any warranty (expressed or implied), representation, inducement, or license except that it is accurate to the best of Green Diamond Performance Materials knowledge. This information is offered solely for your consideration, investigation, and verification. Any use of this information must be determined by the user to be in accordance with applicable federal, state, and local laws and regulations. Furthermore, the conditions or methods of handling, storage, use and disposal of the product are beyond the control and knowledge of Green Diamond Performance Materials. Green Diamond Performance Materials does not assume responsibility and expressly disclaim liability for any loss, damage, or expense arising out of or in any way connected with the handling, storage, use, or disposal of the product. Buyer assumes all risks in its use of the product.