STICS

I

ERS

Stainless-steel and brass unloader with adjustable pressure valve and forged brass manifold



Powder coated steel mounting plate with center balanced lift and four (4) rubber isolators





Electric Models

Pump: Direct drive triplex piston General pump with ceramic plungers · Thermal relief valve · Safety relief valve · In-line water strainer · Adjustable low pressure detergent injection · Pump accepts incoming water up to 180°F (2MUH models)

Motor: Totally enclosed fan-cooled electric motor with thermal overload protection · 35-foot, 15-amp power cord (20-amp plug on CD-1502 models) with ground fault circuit interrupter (GFCI)

Accessories: Variable high/low pressure nozzle with adjustable spray pattern (15-degree high/low pressure nozzle on 2MUH models) · 25-foot x %-inch non-marking hose with quick connects, swivel and bend restrictors · Professional-grade insulated trigger gun with safety lock-off · 36-inch two-piece insulated wand

Gasoline Model

Pump: Direct drive triplex piston General pump with ceramic plungers \cdot Thermal relief valve \cdot Safety relief valve \cdot In-line water strainer \cdot Adjustable low pressure detergent injection

Engine: Performance-proven Honda OHV engine with low-oil protection

Accessories: Quick connect nozzles (0°, 15°, 25° and detergent nozzle) \cdot 50-foot x %-inch non-marking hose with quick connects, swivel and bend restrictors \cdot Professional-grade insulated trigger gun with safety lock-off \cdot 36-inch two-piece insulated wand



Performance Under Pressure."

PORTABLE - HAND CARRY - ELECTRIC/GASOLINE - DIRECT DRIVE

Model No.	PSI	GPM	HP/Motor	Plug Type	Dimensions (LxWxH)	Ship Wt.	Net Wt.
CD-1002-0MUH	1000	2.0	1.5/120V, 1Ø, 12.5A	NEMA 5-15P	20in.x11.5in.x14in.	70 lbs.	58 lbs.
CD-1002-2MUH	1000	2.0	1.5/120V, 1Ø, 12.5A	NEMA 5-15P	20in.x11.5in.x14in.	71 lbs.	66 lbs.
CD-1502-0MUH	1500	2.0	2.0/120V, 1Ø, 17.0A	NEMA 5-20P	20in.x11.5in.x14in.	76 lbs.	70 lbs.
CD-1502-2MUH	1500	2.0	2.0/120V, 1Ø, 17.0A	NEMA 5-20P	20in.x11.5in.x14in.	76 lbs.	70 lbs.
9.50							

*Pump accepts incoming water up to 180°F.

Model No.	PSI	GPM	Displacement/Engine	Dimensions (LxWxH)	Ship Wt.	Net Wt.
CD-2003-0MHH	2000	2.7	196cc Honda OHV	18in.x14.5in.x18in.	75 lbs.	56 lbs.

CD-2003-0MHH	2000	2.7	196cc Honda OHV	18in.x14.5in.x18in.	75 lbs.	56 lbs.

Optiono	
18-0370, 18-0371	Rotating nozzle - Increase your cleaning power and decrease your cleaning time
50-0161	High pressure detergent injection - High pressure water mixes with detergent to clean even the heaviest build-up
CX-0030	50-foot high pressure hose - For when you need extra hose for added mobility

Model #	18-0370	18-0371	50-0161	CX-0030
CD-1002		•	•	•
CD-1502	•		•	•
CD-2003			•	



15-amp plug



NEMA 5-20P, 20-amp plug





HONDA ENGINE WARRANTY







ELECTRIC MOTOR WARRANTY





Gasoline Model