

## SECTION 1: MANUFACTURER, PRODUCT IDENTIFICATION

Manufacturer's Name: Advanced Protective Products Inc.  
Address: 187 Warren Street, Jersey City, NJ 07032  
Information Phone: 201-435-6166.  
In U.S.A (800) 255-3924 International: (813) 979-0626  
Manufacturer's Duns No. 10-758-5838

Product Name: **RUST DESTROYER**<sup>?</sup>

Product Code: 999

Heat Resistant up to 800°F Rust Converting Paint Primer.

Chemical Family: Special Alkyd Emulsion Base Primer.

HMIS CODE	SARA TITLE 312	
Health:	1 Acute:	No
Flammability:	2 Chronic:	Yes
Reactivity:	0 Fire:	Yes
Personal Protection:	G React:	No

## SECTION 2: INGREDIENTS, HAZARDOUS INGREDIENTS

INGREDIENT	MAX%	CAS NO.	TLV	PEL	STEL CEIL	MM HG TEMP
Stoddard Solvent (f,n)	20.0	8052413	100 PPM	100PPM		2.0 @ 20°C
Silica Crystalline (f,*)	0.3	14808807	.1MG/M <sup>3</sup>	.1MG/M <sup>3</sup>		N/A
11 Iron Oxide (f,*,n)	9.22	1309-37- 1	5MG/M <sup>3</sup>	5MG/M <sup>3</sup>		N/A
Calcium Carbonate(*)	31.25	1317-65- 3		5MG/M <sup>3</sup>		N/A

### II Federal Regulatory Information:

OSHA Status: this Product Is Hazardous under the Criteria of the Federal Osha Hazard Communication Standard 20 CFR 1910. 1200.

TSCA Status: on TSCA Inventory.

Cercla Reportable Quantity: None.

Sara Title III: Section 302 Extremely Hazardous Substances: None

Section 311/312: Hazard Categories: Non Hazardous under Section 311/312  
Section 313: Toxic Chemicals: None

f Federal Hazard List

\* Hazardous Only as Dust When Product Is Sanded.

3 Section 313 of the Emergency Planning & Community Right to Know Act of 1986  
and of 40 CFR 372

n New Jersey Label Law Hazardous Chemical

CAS REGISTRY#	% W % V	CHEMICAL	NAME(S)	CARCINOGEN LISTING IN NTP, IARC, OSHA 1910 (Z) SPECIFY
1309-37-1	10	Pigments	Iron Oxide*	Not Listed
64741-41-9	38	Vehicle	Special Alkyd Emulsion	Not Listed
8052413	20	Solvent Aliphatic	Not Listed	
5979-41-5	5	Others	Calcium Boro Silicates	Not Listed
13-17-65-3	27	Others	Calcium Carbonate	Not Listed

### SECTION 3: PHYSICAL DATA

Boiling Point of Vehicle: 380°F+. Specific Gravity: (H<sub>2</sub>O=1) 1.28  
Vapor Pressure: @68°F 2 MM HG. Volatile by Volume: % 34  
Solid by Weight: % 64 Vapor Density: Heavier than Air  
Evaporation Rate: Slower than Ether. Solubility in Water: None  
pH = 7. Material Is Liquid. Appearance and Odor: Red Oxide Primer, Mild Aliphatic  
Solvent Odor

### SECTION 4: FIRE AND EXPLOSION HAZARD DATA

DOT Flammability Classification: Combustible  
Flash Point: 105°F, 46°C. Method Used Seta Closed Cup  
Explosive Limits: Lower 1.0% Upper 6.0%  
Extinguishing Media: Foam, CO<sub>2</sub>, Sand.  
Special Fire Fighting Procedures: Avoid water, oxidizing agents!  
Cool exposed containers with water. Use self contained breathing apparatus.  
unusual fire and explosion hazards: closed container May burst if exposed to extreme  
heat or fire. Toxic gases may form when product burns.

### SECTION 5: HEALTH HAZARD DATA

**Effects of over Exposure Acute:**

Inhalation: inhalation of vapors, may effect the brain or nervous system, causing nausea, dizziness, headache, respiratory irritation.

Eye contact: causes eye irritation

Skin contact: causes skin irritation

Ingestion: irritation of the digestive tract and nervous system depression (drowsiness, dizziness, loss of coordination, fatigue).

Aspiration hazard: this material can enter lungs during swallowing or vomiting and cause lung inflammation and damage.

**Effects of over Exposure Chronic:**

Skin contact: prolonged or repeated exposure may cause dermatitis.

Inhalation statement: sanding dust inhalation may cause lung damage. Crystalline silica has been classified as probably carcinogenic for humans (2a) by IARC.

Notice: reports have been associated permanent brain and nervous system damage with repeated, prolonged overexposure to solvents among persons engaged in the painting trade. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

**Medical Conditions Prone to Aggravation by Exposure:**

none expected when used in accordance with safe handling and use information. (Section 8)

**Primary Route(s) of Entry:**

Dermal, Inhalation, Ingestion.

**Emergency and First Aid Procedures:**

Inhalation: take person to fresh air, maintain breathing, get medical attention.

Eye contact: wash immediately with large amounts of water or eyewash, get medical attention.

Swallowing: get medical attention.

Threshold limit value: 100 PPM. Permissible exposure limit: 500 PPM

**SECTION 6: REACTIVITY DATA**

Stability: stable hazardous polymerization will not occur.

Hazardous decomposition products: burning may produce CO<sub>2</sub>, CO.

Conditions to avoid: elevated temperatures, build up of vapors.

Incompatibility: (materials to avoid) water, oxidizing agents

**SECTION 7: SPILL OR LEAK PROCEDURES**

Steps to be taken in case material is spilled/released: remove all sources of ignition.

Avoid breathing vapors. Add solid absorbent. Use non sparking tools. Shovel, scoop in disposal cart, hose down area.

Waste disposal method: place in appropriate disposal facility, in compliance with federal,

state, local regulation.

## **SECTION 8: SAFE HANDLING AND USE INFORMATION**

Respiratory protection: wear NIOSH approved respiratory suitable for protection against paint spray mist, organic vapors, sanding dust in restricted or confined areas.

Ventilation: adequate to maintain working atmosphere below T.L.V. and L.E.L. (See section 2 for ingredient data and concentrations). Mechanical exhaust may be required in confined areas. Discharge exhaust only in area away from ignition sources.

Protective gloves: solvent impermeable gloves are required during repeated contact.

Eye protection: splash goggles or safety glasses with slide shields

Other protective equipment: clothing adequate to protect skin.

Hygienic practices: remove and wash clothing before reuse. Wash hands before eating, smoking, or using the washroom.

## **SECTION 9: SPECIAL PRECAUTIONS**

### **Precautions to Be Taken in Handling and Storage:**

Store at room temperature. Keep from freezing, excessively low or high temperature, sparks, open flame.

### **Other Precautions:**

Use only with adequate ventilation. Avoid prolonged contact with skin and breathing of vapor spray mist or sanding dust. Close container after each use. Keep out of reach of children. Do not take internally.

While advanced protective products believe that the data set forth herein are accurate as of the day hereof, advanced protective products makes no warranty with respect thereto and expressly disclaims all liability for reliance thereon. Such data are offered solely for your consideration.

The information in this material safety data sheet concerning health hazard data was obtained from sources believed to be reliable. However, the information is provided without any representation or warranty, expressed or implied, regarding its accuracy or correctness. Once this product leaves our plant, the conditions or methods or handling, storage, use the disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage, or expense arising out of or in any way connected with the handling, storage, use or disposal of the product.

NAME:Walter Landzettel  
TITLE: SAFETY CONSULTANT

DATE: May 3, 2004